

Technibond Limited

Millboard Road Bourne End

Buckinghamshire SL8 5XD England

Tel 01628 642800 Fax 01628 642801

www.technibond.co.uk email sales@technibond.co.uk

Technibond
bonding industry together

Techniseal
self adhesive
foam sealants



Technibond
bonding industry together

Techniseal

Self adhesive foam sealants



- Cushioning
- Sound insulation
- Water seals
- Air seals
- Dust seals
- Light seals
- Abrasive protection
- Electrolytic insulation
- Draught seals
- Anti-vibration insulation
- Security bonding

Techniseal

330

High density PVC foam water and weatherseal, coated on the face side with an acrylic pressure sensitive adhesive for easy positioning. A removable support liner on the other side prevents stretch during application. For heavy duty sealing and cushioning applications, thin joints, and die cut gaskets.

Widths: 6mm to 1400mm
Thicknesses: 1.5mm, 3mm, 4.5mm and 6mm
Colours: Black (TSB 330)

Techniseal

220

Medium density PVC foam air, dust and weatherseal, coated on the face side with an acrylic pressure sensitive adhesive for easy positioning. A removable support liner on the other side prevents stretch during application. For general sealing and cushioning applications, can be cleanly drilled through for mechanical fixing.

Widths: 6mm to 1400mm
Thicknesses: 3mm, 4.5mm and 6mm
Colours: Black (TSB 220), White (TSW 220) and Grey (TSG 220)

Techniseal

200M

Medium density PVC foam air, dust and moderate weatherseal coated on the face side with an acrylic pressure sensitive adhesive for easy positioning. A fixed polyester support liner on the other side prevents stretch during application and allows the seal to be re-opened and re-closed many times.

Widths: 6mm to 1000mm
Thicknesses: 3mm, 4mm, 5mm and 6mm
Colours: Black (TSB 200M) and White (TSW 200M)

Techniseal

110

Low density very soft PVC foam air, dust and light weatherseal, coated on the face side with an acrylic pressure sensitive adhesive for easy positioning. A removable support liner on the other side prevents stretch during application. For general sealing applications, particularly for large gaps and thin materials.

Widths: 6mm to 1400mm
Thicknesses: 3mm, 4.5mm, 6mm, 10mm, 12mm, 15mm and 20mm
Colours: Black (TSB 110) and Grey (TSG 110)

Techniseal

SGT

High density PVC foam coated on both sides with an extra strong acrylic pressure sensitive adhesive for use as a security glazing tape on uPVC windows.

Widths: 6mm to 1000mm
Thicknesses: 3mm, 4.5mm and 6mm
Colours: Black

Techniseal

PE

A range of polyethylene foams coated on one side with a strong rubber based adhesive. Available in a range of densities, colours and thicknesses to suit many protection, cushioning, dust- and light-sealing applications.



Full product data sheets available on request. Contact us today on:
01628 642800 or visit www.technibond.co.uk